

Lubricant RX-72 TLX



Description

RX-72TLX is a blend of non-ionic and anionic surfactants in an aqueous solution.

RX-72TLX is designed to reduce metal / metal friction.

RX-72TLX is suitable for use in sea water, brines and drilling fluids.

RX-72TLX is the latest of our wide range of Lubricants. Due to extended reach, high angle and deep water wells being drilled today, lubricants are becoming a necessity with regard to wellbore clean-out, wireline operations, coil tubing operations, running production tubing etc.

Discussions with Roemex representatives will allow the most effective product to be recommended and applied in the most appropriate manner.

Application

RX-72TLX may be utilised in a variety of applications to reduce friction:

- Is stable to 165 deg.C
- Compatible with nitrile elastomers
- Has been used in both oil and gas wells
- Has been premixed with diesel
- Used successfully in drilling fluids
- In coiled tubing, wireline, snubbing and completion installation operations
- May be used as a well clean-up spacer

Roemex representatives should be consulted regarding specific recommendations for each operation.

Properties

Specific Gravity	1.05
Flash Point	>62 deg C (Non Flammable)
Pour Point	<-0 deg C
pH	7-8
Appearance	Clear liquid
Hazard Class	Non-hazardous

Handling

No special procedures need to be observed. Normal precautions should be taken and protective clothing, goggles and PVC/rubber gloves should be worn.

Packaging

Available in 208 litre steel drums, 1,000 litre IBC's or in exact quantities supplied in tanks of up to 4,500 litre capacity.